

SHINGLE CLADDING

DATA SHEET

An impressive profile on any project, Shingle Cladding shares an identical profile design to flatlock, but once folded and installed, a completely different wall system presents itself.

Shingle panels can be folded into interconnecting diamond tile shaped patterns. A highly decorative and intricate system, this system achieves patterns not possible with any other sheet metal system.

Material Availability

KME Copper | VM Zinc | COR-TEN | Aluminium | COLORBOND® | COLORBOND® Ultra | ZINCALUME®
UniCote® | MagnaFlow® | UniCote® LUX

General Requirements

- Material thickness varies but generally ranges from 0.5mm to 1.0mm
- Normally installed to a ventilated plywood substrate, but other substrates can be considered
- Continuous wall studs or Top hats at max 600mm spacing.
- Plywood 17mm structural to as 2269
- Fully breathable / waterproofed membrane
- Fix at lock clips at max. 300mm centres. Clips to be same material as panels
- 140 mm - 340 mm standard shingle sizes with custom sizes available on request
- Panels are laid diagonal



Not to scale



ARCHITECTURAL
Roofing + Building Supplies

A: 1/13 De-Havilland Cres, Ballina NSW 2478

P: 02 6686 4884

E: sales@architecturalroofing.com.au

W: architecturalroofing.com.au